

CENTURY GEOPHYSICAL LLC. PRODUCT DESCRIPTION

9804 Series Acoustic Televiwer



Background Information

The Acoustic Televiwer takes an oriented "picture" of the borehole using high-resolution sound waves. This acoustic picture is **displayed** in both amplitude and travel time. This information is used to detect bedding planes, fractures, and other hole anomalies without the need to have clear fluid filling the boreholes. The televiwer digitizes 256 measurements around the borehole at each high-resolution sample interval (.005 meters/.02 feet). This data is oriented to North and displayed real-time while logging using the Visual Compu-Log software. Analysis includes color adjustment, fracture dip and strike determination, and classification of anomaly. It allows information to be **displayed** on the graphical screen, plot, and in report format. Optionally, the tool can be equipped with a natural gamma sensor.

Features

Properties Measured (see diagram)	Tool Specifications
<p>1. Natural Gamma: Offset: 20.42cm (8 in.)</p> <p>Scintillation (NG): 0 to 10,00 API, Accuracy +/-5 percent</p> <p>2. Deviometer: Offset: 213.4 cm (84 in.)</p> <p>X-Y Inclinometer (XYI): 0 to 90 degrees, Accuracy +/-0.5 degrees</p> <p>Azimuth (AZ): 3-axis magnetometer 0 to 360 degrees, Accuracy +/- 2 degrees</p> <p>3. Acoustic Amplitude & Acousitic Travel Time: Offset: 213.4 cm (84 in.), Accuracy +/- 2.55 mm (0.1 in.)</p>	<p>Outside Diameter 50.8 mm (2 in.)</p> <p>Weight: 14 kg (30 lbs.)</p> <p>Length: 225 cm (88.5 in.)</p> <p>Pressure: 105 kg/cm² (1500 psi)</p> <p>Temperature: 85 C (185 F)</p> <p>Scan Rate: 12 revolutions/second</p> <p>Sample Rate: 256 samples/revolutions</p> <p>Borehole Size: 74 to 230 mm (2.9 to 9 in.)</p> <p>Logging Speed: 3 m/min (10 ft/min.)</p> <p>Tool Voltage Required: 115 VDC</p>

Tool Information

Item	Model #	Part #
Tool with Acoustic Televiwer, XYI, AZ	8804	332004B
Tool with Acoustic Televiwer, XYI, AZ, and Natural Gamma	9804	332004A
Deviation calibration test stand		317420